

Brakemeter / Dynamometer

TRANSAFE
TECHNOLOGY

SINCE / DEPUIS 1985

TranSafe Technology
2880 Argenta Road, Unit 3
Mississauga, ON, L5N 7X8

Tel. 905-826-8099 / Fax 905-826-1778

www.transafetech.com



- Replaces the Tapley Mete
- Hand-made precision instrument
- Windscreen suction cup
- Measures deceleration & acceleration
- Portable
- DVSA-approved
- Easy to Use
- For Vehicle Classes 3, 4, 5 & 7
- Heavy base available
- Wooden carry case available

Overview

The Brakemeter / Dynamometer is a hand-made precision instrument that mechanically measures both deceleration and acceleration. The instrument consists of a finely balanced pendulum, free to respond to any changes in speed or angle, working through a quadrant gear train to rotate a needle round the dial. The dial is black with silver white graduations and has a linear length of 5 1/2 inches (114 mm). The unit is filled with a special fluid which damps out all vibration. Other than a calibration every 2 years, which is carried out by Bowmonk, no maintenance is necessary.

The dial is calibrated in percentage "G", the accepted standard throughout the world for measuring acceleration and deceleration. There are no connections to the vehicle other than mounting - either with two self-tapping screws onto a heavy stand or by using the suction cup operated by the small side lever.

In the UK, Bowmonk brake meters are approved by the DVSA for use in the annual MOT vehicle-testing scheme. Wherever brake testing is mandatory by law the Bowmonk Brakemeter/Dynamometer is an approved brake test instrument. We are a fully approved UKAS testing laboratory and we recalibrate and repair the Brakemeter/Dynamometer, the Tapley meter, and our newer electronic decelerometers.

Test Procedure

Test the vehicle on reasonably level road. The meter is set to zero by releasing the thumbnut, tilting the bowl in its pivots until the main needle points to zero and re-tightening the thumbnut. The meter is now ready for use. It is not necessary to watch the instrument continuously as it is fitted with a recording needle. Depending on the test to be performed the recording needle is positioned to left or right of the main needle by turning the centre chrome knob, and will accurately record the maximum deceleration/acceleration reading.

Part Codes

Bowmonk Brakemeter / Dynometer (Mk III)

Part Code: BOW001

Mechanical instrument for measuring deceleration and acceleration.

Stand for Brakemeter

Part Code: BOW002

A heavy base to which the BOW001 Brakemeter can be secured, if not using the built-in suction cup.

Kit (Brakemeter & Stand)

Part Code: BOW003

This part code can be used to order parts BOW001 and BOW002 together.

Wooden carry case for Brakemeter & Stand

Part Code: BOW004

A sturdy wooden carry case which accommodates both the BOW001 Brakemeter and the BOW002 stand.

Complete Kit (Brakemeter, Stand & Carry Case)

Part Code: BOW005

This part code can be used to order parts BOW001, BOW002 and BOW004 together.

Additional Images



Brakemeter fitted to the BOW002 Stand



Brakemeter Kit (BOW005)



Brakemeter mounted to windscreen using its built-in suction cup.